



TECHNICAL DATA

RENWRAP[®] 319, 327, 327 Aerosol, 328

Primers

DESCRIPTION

RENWRAP 319 is a primer recommended for machine application to new or smooth pipe services and promotes high bond of the RENWRAP pipeline coating to the pipe.

RENWRAP 327 is a primer recommended for use on all hand brush applications with RENWRAP pipeline coatings. It can also be used in machine applications to rough, reconditioned surfaces where a higher solids content is needed.

RENWRAP 327 Aerosol is an aerosol primer that can be used with all RENWRAP pipeline coatings. It is generally used on small diameter pipe services and irregular fittings where ease of application is beneficial.

RENWRAP 328 is a primer recommended for use with RENWRAP pipeline coatings. Used for non-flammable applications where extreme safety precautions are being observed.

TECHNICAL PROPERTIES

	319	327	327 Aerosol	328
Base Adhesive System	Synthetic rubber and resins	Synthetic rubber and resins	Synthetic rubber and resins	Synthetic rubber and resins
Solvent System	Heptane/Toluene	VM & P Naphtha/Toluene	VM & P Naphtha/Toluene	Trichloroethylene
Total Solids	19%	27%	27%	11%
Viscosity	Thin Syrup	Medium Syrup	Medium Syrup	Thin Syrup
Flash Point	-12°C (+10°F)	-4°C (+40°F)	-4°C (+40°F)	Non-Flammable
Color	Black	Black	Black	Black
Shelf Life	Excellent	Excellent	Excellent	Excellent

Caution: Store away from heat and use away from fire, flames, heaters, sparks, lighted cigarettes, etc. Read all label instructions.

RENWRAP is a Registered Trademark of Scapa North America

05-08

(800) 801-0323 ➤ www.scapana.com ➤ appsupport@scapana.com

The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions. **THE PRODUCTS DISCUSSED HEREIN ARE SOLD WITHOUT ANY WARRANTY AS TO MERCHANTABILITY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED.** No representative of ours has any authority to waive or change the foregoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.