

Pig Trackers are devices that are used to track the passage and pinpoint a pipeline pig that is equipped with an appropriate transmitter. These devices enable operating and maintenance companies to minimize the costs involved with excavating and removing stuck pigs.

The Model 4 System is designed for pipe sizes 6 inches to 12 inches. This system includes the PT-275 Transmitter, especially designed to fit poly (foam) and urethane pigs. The PT-275 transmitter negotiates line sizes of 6 inches to 12 inches.

- 1 – PT275 Transmitter
- 1 – PTR Receiver
- 1 – 1-3 ft. Wand
- 1 – Carrying Case
- 1 – Strap
- 2 – 9v Batteries
- 4 – AA Batteries
- 1 – Crescent Wrench
- 1 – Operating Instruction Manual



To locate a pig equipped with a SPY® Transmitter, the SPY® 23 HZ Receive (Pig Tracker Receiver and Wand) registers the changing magnetic field produced by any SPY® Transmitter. When the Transmitter is located, the 23 HZ Receive produces both an audio and visual output. With two standard 9-volt alkaline batteries, the 23 HZ Receive can be powered continuously for approximately 50 hours. Special waterproof wands are available for sub-sea applications, with depths of up to 10,000 feet [3000 meters].

PROLINE IS A FACTORY AUTHORIZED WARRANTY AND REPAIR FACILITY

**PROLINE PIPE EQUIPMENT INC.**

7141 – 67 STREET EDMONTON, ALBERTA, CANADA T6B 3L7 TELEPHONE: 780-465-6161 FAX: 780-466-3036  
sales@proline-global.com www.proline-global.com