



| Catalog No. | Item Code | Pipe Capacity |                | Length |     | Weight |      |
|-------------|-----------|---------------|----------------|--------|-----|--------|------|
|             |           | in-nom.       | actual O.D. mm | in     | mm  | lbs    | kg   |
| H2 1/2S [1] | 03110     | 1 - 2 1/2     | 32 - 76        | 17     | 419 | 7.2    | 3.3  |
| H21/2I [1]  | 03112     | 1 - 2 1/2     | 32 - 76        | 17     | 419 | 7.2    | 3.3  |
| H21/2X [1]  | 03114     | 1 - 2 1/2     | 32 - 76        | 17     | 419 | 7.2    | 3.3  |
| H4S         | 03120     | 2 - 4         | 60 - 125       | 22     | 559 | 12.8   | 5.8  |
| H4I         | 03122     | 2 - 4         | 60 - 125       | 22     | 559 | 12.8   | 5.8  |
| H4X         | 03124     | 2 - 4         | 60 - 125       | 22     | 559 | 12.8   | 5.8  |
| H6S [2]     | 03130     | 4 - 6         | 114 - 182      | 28     | 711 | 19.4   | 8.8  |
| H6I         | 03132     | 4 - 6         | 114 - 182      | 28     | 711 | 19.4   | 8.8  |
| H6X         | 03134     | 4 - 6         | 114 - 182      | 28     | 711 | 19.4   | 8.8  |
| H8S         | 03140     | 6 - 8         | 168 - 240      | 32     | 813 | 24.4   | 11.1 |
| H8I         | 03142     | 6 - 8         | 168 - 240      | 32     | 813 | 24.4   | 11.1 |
| H8X         | 03144     | 6 - 8         | 168 - 240      | 32     | 813 | 24.4   | 11.1 |
| H8XX        | 03146     | 6 - 8         | 168 - 240      | 32     | 813 | 24.4   | 11.1 |
| H12S        | 03150     | 8 - 12        | 219 - 356      | 34     | 864 | 34.9   | 15.9 |
| H12I        | 03152     | 8 - 12        | 219 - 356      | 34     | 864 | 34.9   | 15.9 |
| H12X        | 03154     | 8 - 12        | 219 - 356      | 34     | 864 | 34.9   | 15.9 |
| H12XX       | 03156     | 8 - 12        | 219 - 356      | 34     | 864 | 34.9   | 15.9 |

[1] EXCLUSIVE SIZE

[2] H6S with regular HS6 cutter wheels works great for cutting 4" - 6" copper, types K & L.

**NOTE:**

S= includes cutter wheels for steel;

I= includes cutter wheels for cast and ductile iron;

X= includes cutter wheels for schedule 80 steel;

XX= for schedule 100 steel.

**FEATURES**

- Another Reed invention that needs only 4" (102 mm) of clearance around pipe.
- Efficient handle swing of only 90° to 110°.
- Can be used anywhere - in the ditch, underwater, overhead, in racks of pipe!

Wheels for same size cutters are interchangeable. Recommend only Reed cutter wheels be used with these hinged cutters. Reed wheels are made from high shock-resistant tool steel on computerized (CNC) machines and then precisely heat treated. This allows for a thinner profile yet stronger blade, so they:

- Cut easier and faster, especially stainless steel and ductile pipe.
- Last much longer.
- Allow for shorter cutter handle for work in tight spaces.
- Provide the best value.



**PROLINE PIPE EQUIPMENT INC.**