


NC3032 INTERNAL PNEUMATIC LINE-UP CLAMP (Self-Propelled Travel)



FEATURES:

- The Proline NC3032 Internal Pneumatic Line-up Clamp assures a rapid, accurate alignment of two pipes prior to welding. It is designed using the latest in technology and materials to withstand the most extreme field conditions associated with pipeline construction.
- Large air cylinders power the expander sections of the clamp for superior clamping and alignment of the pipes.
- Expander sections operate independently to lock the clamp in position.
- Specially designed shoes on each expander section exert pressure uniformly around the inside circumference of the pipe to force it into roundness.
- Designed to traverse through tight bends.
- Easily adjustable for any wall thickness within specified range.
- Travels through the pipe to the next joint under its own power.
- Large capacity air tank for extended travel in double-jointed pipes.
- Side drag brakes for extreme grade.
- Comes with tubular reach rod for remote actuation of the air valves.

SPECIFICATIONS:

- Pipe size range: 30 inch nominal (762.0 mm) to 32 inch nominal (812.8 mm)
- Pipe wall thickness range: 0.188-0.875 inch (4.8-22.6 mm)
- Length: 117 inches (2972 mm)
- Width: 30 inches (762 mm)
- Height: 30 inches (762 mm)
- Weight: 1275 pounds (579 kg)
- Recommended working air pressure: 180-200 pounds/in. (12.4-13.8 bar)
- Air Receiver Capacity 110L
- Grade climbing capability: 20 degree