

PROLINE FLANGE ALIGNING TOOLS are a safe, fast, and effective solution for even the toughest flange alignment jobs. The tool's tapered shaft is a patented feature that eliminates the need for hammering and prying when lining up flange bolt holes. PROLINE Flange Aligning Tools are sold individually and in sets.



PROLINE Flange Aligning Tool

CATALOG NO.	BOLT HOLE SIZE	LENGTH	WEIGHT
FT00	3/8"	2-1/8"	1-1/4 ozs.
FT0	1/2"	2-3/8"	2-1/4 ozs.
FT01	5/8"	2-3/4"	4 ozs.
FT02	3/4"	3-1/4"	7 ozs.
FT03	7/8"	3-1/2"	11 ozs.
FT04	1"	4"	1 lb.
FT06	1-1/8"	5"	1-1/2 lbs.
FT08	1-1/4"	5-1/2"	2 lbs.
FT1012	1-3/8"	6-1/4"	2-7/8 lbs.
FT14	1-1/2"	6-1/2"	3-1/4 lbs.
FT16	1-5/8"	7-1/4"	4-1/8 lbs.
FT1820	1-3/4"	7-7/8"	4-3/4 lbs.
FT22	1-7/8"	8-3/8"	7 lbs.
FT2426	2"	9"	6-5/8 lbs.
FT30	2-1/8"	12"	10-3/8 lbs.
FT34	2-3/8"	13-1/4"	13-1/8 lbs.
FT3642	2-5/8"	14"	16-7/8 lbs.
FT48	2-7/8"	13-5/8"	24-3/8 lbs.
FT5054	3-1/8"	18"	35-7/8 lbs.
FT60	3-5/8"	20"	54-7/8 lbs.

EXTRA LONG

FT0L	1/2"	5-3/8"	10 ozs.
FT01L	5/8"	5-3/4"	12 ozs.
FT02L	3/4"	6-1/4"	14 ozs.
FT03L	7/8"	6-1/2"	1-1/8 lbs.
FT04L	1"	7"	1-1/2 lbs.
FT06L	1-1/8"	8"	2-1/4 lbs.
FT08L	1-1/4"	8-1/2"	3 lbs.
FT1012L	1-3/8"	9-1/4"	4 lbs.
FT14L	1-1/2"	9-1/2"	4-1/2 lbs.
FT16L	1-5/8"	10-1/4"	5-3/4 lbs.
FT1820L	1-3/4"	10-7/8"	6-1/4 lbs.
FT22L	1-7/8"	11-3/8"	7-1/2 lbs.
FT2426L	2"	12"	9-1/4 lbs.
FT30L	2-1/8"	15"	13 lbs.
FT34L	2-3/8"	16-1/4"	15 lbs.
FT3642L	2-5/8"	17"	18 lbs.

PROLINE Flange Aligning Tool Sets

CATALOG NO.	SET INCLUDES 2 EACH:	WEIGHT
FTS24	FT02, FT03, FT04	8 lbs.
FTS26	FT02, FT03, FT04, FT06	11 lbs.
FTS28	FT02, FT03, FT04, FT06, FT08	15 lbs.
FTS212 (shown)	FT02, FT03, FT04, FT06, FT08, FT1012	21 lbs.
FTS1426	FT14, FT16, FT1820, FT2426	47 lbs.
EXTRA LONG		
FTS24L	FT02L, FT03L, FT04L	17 lbs.
FTS26L	FT02L, FT03L, FT04L, FT06L	21 lbs.
FTS28L	FT02L, FT03L, FT04L, FT06L, FT08L	26 lbs.
FTS212L	FT02L, FT03L, FT04L, FT06L, FT08L, FT1012L	37 lbs.

Simply find a bolt hole that is aligned enough for the tapered shaft to fit through and turn. If necessary, use a second tool and turn until the bolt holes are in alignment and insert the flange bolts.

PROLINE PIPE EQUIPMENT INC.